

# SPECIFICATION SHEET

# Mobilink<sup>™</sup> P80 Plus Portable Receipt Printer



# The fast, rugged, wireless, 3" receipt printer with auto cutter.

**Highly efficient** — built-in auto cutter speeds up transaction time and ensures receipts with clean, smooth edges

**Seamless integration** — compatible with iOS<sup>®</sup>, Android<sup>™</sup> and Windows<sup>®</sup> mobile devices; includes wireless setup with SimpleAP (wireless SKU only)

**Long-life battery** — operational up to 33 hours (Bluetooth<sup>®</sup>), up to 25 hours (wireless)<sup>1</sup>

Ultra fast print speed — prints 3" receipts at up to 100 mm per second

Rugged design - four-foot drop rating, plus IP4X environmental certification

**Easy wireless configuration** — 802.11 a/b/g/n with 2.4GHz/5GHz compatibility, plus Bluetooth 3.0 (EDR Supported)

NFC feature — save time with convenient touch-to-print functionality<sup>2</sup>

Paper-saving options — save up to 23 percent via special utility settings

POS



# Mobilink<sup>™</sup> P80 Plus

# Print

Printing Method Thermal Print Speed 100 mm/s Print Resolution 203 dpi Print Direction Vertical and horizontal

### **Print Fonts**

Fonts/Column capacity 48 cpl mode: Font A: 12 x 24 48 cpl (default); Font B: 9 x 17 64 cpl; 42 cpl mode: Font A: 13 x 24

42 cpl, Font B: 9 x 17 60 cpl Character Size 48 cpl mode: Font A 1.50 x 3.00 mm,

Font B 1.125 x 2.13 mm 42 cpl mode: Font A 1.63 x 3.00 mm. Font B 1.125 x 2.13 mm

Character Set 95 Alphanumeric, 48 International, 128 x 10 Graphic

Barcode UPC-A, UPC-E, JAN13/EAN13, JAN8/EAN8, Code 39, ITF, CODEBAR (NW-7), Code 93, Code 128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

Two-Dimensional Symbol Printing QR Code, Maxi Code, PDF417, Composite symbology, GS-1, Aztec, Datamatrix

### Media Handling

Type Thermal roll paper Paper Feed Method Friction feed Width (Without Spacer) 3.13"/79.5 mm Width (With Spacer) 2.97"/75.5 mm Paper Loading Drop-in Roll Diameter (Max) 2.0"/51 mm Core Diameter (Min) 0.71"/18 mm Paper Guide Yes Auto Cutter Yes

# Connectivity

Interfaces 802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 3.0 (EDR supported)

Wireless Security Mode WEP, WPA, WPA2-Personal/ Enterprise)

Supported Mobile Operating Systems iOS, Android and Windows (Store Apps)

Easy Setting SimpleAP, TM Utility, NFC<sup>2</sup>, and QR Code

# General

Printer Reliability 10 million printing lines Auto Cutter Reliability 500,000 auto cutter IP Rating IP4X

Drop Rating 4 feet

Charging PS-11 charger (2.5 hours to full charge), custom Single bay charger (2.5 hours to full charge) custom quad bay charger (2.5 hours to full charge)

Operational Battery life<sup>1</sup> 25 hours for wireless and 33 hours for Bluetooth

NV Bit Image Memory 192KB (max), NV Graphics 384KB (max) Data Buffer 64KB (Bluetooth)

Notes: No information (limitation) for Wireless model. **Printer Driver** Windows driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux), TM Virtual Port Driver, ePOS-Print SDK

Software TM-P80 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P80 Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page

Audible Alert Programmable Buzzer

**LED Indicators** Blue LED (On = Power, Off = Power Off, Remaining Battery) Orange LED - Error and Battery Charging Sensors Paper End, Cover Open

Power Source Custom lithium-ion battery pack, (optional) PS-11 charger

# **Power Saving Yes**

Temperature 0° C - 45° C (without PS-11 Connection) Relative Humidity 10 - 90 %

# Acoustic Noise Level 55db

Standards and Approvals North America EMI: FCC Class A, ICES-003 Class A Safety standards: UL60950-1/CSA C22.2 No.60950-1

Dimensions (W x D x H) 4.3" x 5.5" x 2.7" 110 x 140 x 69 mm

Weight 1.40 lb/630 g Color Epson Black

# **Options**

Battery OT-BY60II Single Charger OT-SB60II Quad Charger OT-CH60II Power Supply PS-11

# **Eco Features**

Paper Saving Mode Power Saving Mode

#### Warranty

Standard with a one-year limited warranty (excluding battery); optional extended warranty available (excluding battery)

#### What's in the Box

Mobilink P80 Plus, Battery - Model OT-BY60II, Roll Paper (For checking initial movement of the printer), Users Manual, USB Cable, Belt Clip - already attached to printer

# **Ordering Information**

P80 PLUS WiFi Receipt with Auto Cutter P80 PLUS BT Receipt with Auto Cutter

C31CD70311

# C31CD70751

<u>Mobile Receipt Printer</u>

1 Battery life can vary significantly depending on usage. | 2 NFC tag requires use of a device that includes an NFC reader, and may require additional software. | 3 For convenient and reasonable recycling options, visit www.epson.com/recycle | 4 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency

# Better Products for a Better Future eco.epson.com



Epson America, Inc.

Epson Canada Limited 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

EPSON and ESC/POS are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. ePOS and Mobilink are trademarks of Epson America, Inc. Android is a trademark of Google Inc. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-50232 8/15

