

# FUJITSU Image Scanner fi-7600

Heavy-duty & flexible production scanner  
for professional use



## ■ fi-7600 Features


### Stable and smooth scanning of a large volume of documents or various types of documents

The fi-7600 allows you to scan A4 landscape documents at 100 ppm/200 ipm (200/300 dpi). The scanner is suitable for continuous scanning because it allows you to load up to 300 sheets of documents at a time. It helps improve efficiency for scanning a large volume of documents. In addition, various types of documents, such as thin paper, plastic cards envelopes, and long page documents can be scanned on this scanner.

### ■ Mechanism for stable paper feeding and ejecting that prevents document damage and paper feeding failure

#### ● Scan various types of business documents with a single scanner

The straight paper path structure that reduces the load on a document that is being fed, assures stable scanning regardless of the condition and type of a document. By simply changing the feed mode to non separation mode, you can easily scan thick documents such as drawings folded in half, multi-layered receipts, and envelopes with the same straight paper path operation.



Straight paper path

#### ● Protect important information by preventing missing edges and document damage

Skew Reducer helps improve the feeding performance significantly and prevents a scanned image from missing an edge. Paper Protection minimizes the risk of document damage and protects your important documents by detecting abnormalities in sound and document length.

### ■ Design that meets the user's needs

The fi-7600 helps improve the efficiency of operations by providing a variety of functions that make scanning easier for the user.

#### ● Fully utilize allocated space with its flexible design

The operation panels are equipped on the both right and left sides so that a user can easily load documents for scanning to suit the user's office or workspace environment. LCD on the operation panel allows to easily check the status of the scanner.



LCD panel

#### ● Reduce the workload before and after scanning from setting to collecting documents

When setting documents, you can easily align the edges of the documents with independent side guides even if the size of each document varies. For collecting documents, Stacker Side Guide reduces the time and effort that are required for aligning and putting away documents after a scan to prevent ejected documents from being unevenly stacked or aligned.

### ■ Advanced software for your work efficiency

#### ● Connect your business workflow with PaperStream IP and PaperStream Capture

The PaperStream IP scanner driver, which supports TWAIN/ISIS, avoids the inconvenience of fine setting adjustments for OCR processes. It automatically converts the images into exceptionally clean images, accelerating OCR even when scanning wrinkled or soiled documents, or documents with a background pattern. With an intuitive interface, PaperStream Capture effectively and efficiently allows you to feed information into your organization's workflow through various capture features during batch scanning.

#### ● Barcode recognition, automatic sorting, and indexing

You can focus on routine tasks (batch scanning) and configure the scanner to create folders that are divided with barcodes or patch codes as well as automatically sort scanned images to save or index them. The automatic selection of a scanning mode according to each patch codes allows you to load a mixed batch of documents with different types of documents at the same time. The usability for administrators and users is taken into consideration for image processing, which has made simple operations possible and has improved productivity, so that less work is required for users to sort scanned images.

## ■ fi-7600 Technical Specifications

Description		fi-7600
Supported operating systems		Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit)
Scanner type		ADF (Automatic Document Feeder)
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome
Image sensor type		Color CCD (Charge-coupled device) x 2 (front x 1, back x 1)
Light source		White LED Array x 4 (front x 2, back x 2)
Multifeed detection		Ultrasonic multi-feed detection sensor, Paper detection sensor
Paper protection		Warp detection, iSOP (intelligent sonic paper protection)
Document size	Maximum	304.8 x 431.8 mm (12 x 17 in.)
	Minimum	50.8 x 69 mm (2 x 2.7 in.) (Portrait)
	Long page scanning (Maximum)*1	304.8 x 5,588 mm (12 x 220 in.)
Paper weight (Thickness)	Paper	20 to 413 g/m <sup>2</sup> (5.3 to 110 lb), A8 size: 128 to 209 g/m <sup>2</sup> (34 to 56 lb)
	Plastic card	Up to 1.4 mm*2
Scanning speed (A4 Landscape)*3	Color*4	Simplex: 100 ppm (200/300 dpi), Duplex: 200 ipm (200/300 dpi)
	Grayscale*4	
	Monochrome*5	
Scanning speed (A4 Portrait)*3	Color*4	Simplex: 80 ppm (200/300 dpi), Duplex: 160 ipm (200/300 dpi)
	Grayscale*4	
	Monochrome*5	
Paper chute capacity (A4 Landscape)*6		300 sheets (A4: 80 g/m <sup>2</sup> or 20 lb)
Background colors		White / Black (switching with command available)
Optical resolution		600 dpi
Output resolution*7	Color (24-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi (driver)*8
	Grayscale (8-bit)	
	Monochrome (1-bit)	
Output format	Color	24-bit
	Grayscale	8-bit
	Monochrome	1-bit
Internal video processing		4,096 levels (12-bit)
Interface		USB 3.1 Gen 1 / USB 3.0 / USB 2.0 / USB 1.1
Connector shape		Type B
Image processing functions		Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None / Red / Green / Blue / White / Saturation / Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge correction, Vertical streaks reduction, Cropping, Dither, Static threshold, Divide Long Page
Power requirements		AC 100 to 240 V ± 10%
Power consumption	Operating mode	64 W or less
	Sleep mode	1.7 W or less
	Auto Standby (Off) mode	0.35 W or less
Operating environment	Temperature	5 to 35 °C (41 to 95 °F)
	Relative humidity	20 to 80 % (Non-condensing)
Dimensions: Width x Depth x Height*9		236 x 432 x 214 mm (9.3 x 17.0 x 8.4 in.)
Weight		11 kg (24 lb)
Included software / drivers		PaperStream IP driver (TWAIN/TWAIN x64/ISIS), 2D Barcode for PaperStream**10, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series*10, Scan to Microsoft SharePoint*10, ABBYY FineReader for ScanSnap*10, Scanner Central Admin
Environmental compliance		ENERGY STAR® and RoHS
Included items		Stacker, ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM

\*1 Capable of scanning documents that exceed Legal sheets in length. Long page scanning supports documents with a length of up to 5,588 mm (220 in.) when the resolution is set to 200 dpi or less. If you split and output a scanned image of a long page document into multiple pages, a document of up to 200m (218.8 yd.) can be scanned.

\*2 Capable of scanning up to 3 cards at a time. (Note: only one embossed card can be scanned at a time)

\*3 Actual scanning speeds are affected by data transmission and software processing times.

\*4 Indicated speeds are from using JPEG compression.

\*5 Indicated speeds are from using TIFF CCITT Group 4 compression.

\*6 Maximum capacity varies, depending upon paper weight.

\*7 Selectable maximum density may vary depending on the length of scanned document.

\*8 When scanning at high resolution (over 600 dpi), some limitations apply to the size of the document that could be scanned, depending on system environment.

\*9 Excluding the ADF hopper and stacker.

\*10 The software can be downloaded from the website designated in the Setup DVD-ROM.

## ■ Options

Description	Parts number	Comments
Post Imprinter (fi-760PRB)*	PA03740-D101	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.

\* The release schedule varies from sales region to sales region.

## ■ Consumables

Description	Parts number	Comments
Brake Roller	PA03740-K010	Lifetime: Every 250,000 sheets or one year. These rollers separate documents as they are being fed into the scanner.
Pick Roller	PA03740-K011	Lifetime: Every 250,000 sheets or one year. These rollers feed documents into the scanner.
Print Cartridge	CA00050-0262	Lifetime: 4,000,000 printed characters fi-760PRB print head

## ■ Trademarks

\* ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions.

\* ISIS is a registered trademark of EMC Corporation in the United States.

\* Microsoft, Windows and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

\* Other company names and product names are the registered trademarks or trademarks of the respective companies.

Visit the fi Series web site for ordering and purchasing information

<http://imagescanner.fujitsu.com>

## ⚠ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
- Be sure to limit the use of this product to listed power ratings.



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.